

**Model** YC-W932DAHBB85NA

### Camera

Image Sensor	1/2.9" Sony IMX323 CMOS
Effective Pixels	1984(H)x1105 (V)
Electronic Shutter	AUTO, 1/25s ~ 1/100000s
Min. Illumination	0.01Lux@F1.2(AGC ON), 0Lux IR on
Day/Night	Auto/Color/(B/W)/Timing
WDR	Digital WDR
White Balance	Auto
AGC/BLC	Support
DNR	2D/3D DNR
Other	Multi-lines OSD, Motion Detection, Privacy Mask, Mirror, Rotate

### Encode

Embedded Solution	Hi3516C
Video Standard	H.264
Video Resolution	Main stream: 1080P/720P@30fps Sub stream: VGA/360P@30fps, etc.
Video Bitrates	32Kbps - 6Mbps, VBR/CBR
Audio Standard	G.711-u

### IR Led

IR Led	5pcs Array IR LEDs
IR Distance	15-20m

### Lens

Focal length	3.6/6mm
--------------	---------

### Optional Function

POE, Audio, etc.

### Network Services

Protocol	HTTP/RTSP/FTP/NFS/SMTP/DHCP/NTP, etc.
P2P	Yes
Web	IE , Firefox, etc.
Media	CMS, Android, IOS
ONVIF	2.4 compatible

### General

Network Port	1-RJ45, 100Mbps, POE optional
Power Supply	12 VDC $\pm$ 10%
Power Consumption	< 5 W
Operating Temp.	-30°C-(+60)°C, 10%-90%RH
Dimension	$\phi$ 94*80mm
Weight	0.32KG