Model	YC-W964AHBB85NA
Camera	
Image Sensor	1/3" OV4689 CMOS
Effective Pixels	2688(H)×1520 (V)
Electronic Shutter	AUTO, 1/25s ~ 1/100000s
Min. Illumination	0.1Lux@F1.2(AGC ON), 0Lux IR on
Day/Night	Auto/Color/(B/W)/Timing
WDR	Digital WDR
White Balance	Auto
Other	AGC,2/3 DNR,Motion Detection, Privacy Mask, Mirror, Flip
Encode	
Embedded Solution	Hi3516D
Video Standard	H.265/H.264
Video Resolution	H265MainStream:15fps@5MP(2592x1944),25fps@4MP(2592x1520),30fps@3MP/1080P/720P Sub stream: VGA(640x480)/360P/QVGA@25fps
Video Bitrates	512Kbps - 6Mbps, VBR/CBR
Audio Standard	G.711-u
IR Led	
IR Led	5pcs Array IR LEDs
IR Distance	15-20m
Lens	
Focal length	Fixed or VF lens
Lens	3.6/6mm
Optional Function	
POE, Audio, Alarm In/Out, SD card, etc.	
Network Services	
Protocol	RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP
P2P	Yes
Web	IE , firefox, etc.
Media	CMS, Android, IOS
ONVIF	2.4 compatible
General	
Network Port	1-RJ45, 100Mbps, POE optional
Power Supply	12 VDC ± 10%
Power Consumption	< 5 W
Operating Temp.	-30℃-(+60)℃, 10%-90%RH
Dimension	φ94*80mm
Weight	0.32KG