

Model **YC-W964AHZ37DA**

Camera

Image Sensor 1/3" OV4689 CMOS
Effective Pixels 2688(H)×1520 (V)
Electronic Shutter AUTO, 1/25s ~ 1/100000s
Min. Illumination 0.1Lux@F1.2(AGC ON), 0Lux IR on
Day/Night Auto/Color/(B/W)/Timing
WDR Digital WDR
White Balance Auto
Other AGC,2/3 DNR,Motion Detection, Privacy Mask, Mirror, Flip

Encode

Embedded Solution Hi3516D
Video Standard H.265/H.264
Video Resolution H265MainStream:15fps@5MP(2592x1944),25fps@4MP(2592x1520),30fps@3MP/1080P/720P
Sub stream: VGA(640x480)/360P/QVGA@25fps
Video Bitrates 512Kbps - 6Mbps, VBR/CBR
Audio Standard G.711-u

IR Led

IR Led 5pcs Array IR LEDs
IR Distance 15-20m

Lens

Focal length Fixed or VF lens
Lens 3.6/6mm

Optional Function

POE, Audio, Alarm In/Out, SD card, etc.

Network Services

Protocol RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP
P2P Yes
Web IE , firefox, etc.
Media CMS, Android, IOS
ONVIF 2.4 compatible

General

Network Port 1-RJ45, 100Mbps, POE optional
Power Supply 12 VDC ± 10%
Power Consumption < 5 W
Operating Temp. -30°C-(+60)°C, 10%-90%RH
Dimension 186*64.7*83.6mm
Weight 0.45Kg