

# NVR-2004HGK

# NVR-2008HGK

# NVR-2016HGK

## Linux Network Video Recorder



### FEATURE

- Support ONVIF, 4K HD Network Video Preview, Storage / Playback
- Support H.265, H.264, IPC Centralize Management includes IPC Parameter Configuration, Information I/O, Audio Intercom and Upgrade, etc.
- HDMI Output Up To 3840x2160; Brand-new UI Interface, One key to open recording;
- Support Instant Playback, Specified Channel Video Playback Under The Preview Screen Without Affecting Other channels;
- Support Event, Query, Playback Recording File; Double Users Certification
- Support HDD Quota and Group Storage Mode, Allocate Different Saving Spaces / Cycle of Recording For Different Channels;

### SPECIFICATION

Model No.	NVR-2004HGK	NVR-2008HGK	NVR-2016HGK
Operation System	LINUX O.S		
Video & Audio Input	Network Video Input 4CH Network Compress Video Input	8CH Network Compress Video Input	16CH Network Compress Video Input
	Audio Input IPC Composite Audio Input		
Video & Audio Output	HDMI Output 1CH, Resolution: 4K(3840*2160)/30Hz, (1920*1080)/60Hz		
	Audio Output 1*RCA Port		
Video & Audio Encode	Video Standard H.265 /H.264 /MJPEG		
	Recording Resolution 8M/5M/3M/1080P/720P		
	Decode Playback Up To 4CH 1080P Playback		
Recording	Record/Snapshot Manual Recording, Timer Recording, Event Recording, Motion Detection Recording, Alarm Recording		
	Playback Instant Playback, Routine Playback, Event Playback, External File Time-Phased Playback, Routine Playback, Event Playback, External File Playback, Log Playback		
	Backup Routine Backup, Event Backup, Record Cutting Backup		
HDD	HDD Port 2*SATA Ports		
	Max Capacity Each Port supports Max. 6TB HDD		
External	Network Port 1 Port, RJ45 1*RJ45		
	USB Port 3 Ports(1*USB2.0 Port in Front, 2*USB2.0 Ports at Back-end)		
	Serial Port 1* RS-485 1*RS-485		
	Alarm Input 4CH Alarm Input, Low Electrical Level Effective, Green Connection Line Port		
	Alarm Output 1CH Alarm Output, Relay Touch (1A@24VDC), NO, NC can Program		
Network	Network Protocol ONVIF(2.4), IPv4, UPnP(Plug & Play), NTP(Network Timing), SADP(Auto Search IP Address), PPPoE(Dial-up), DHCP(Auto get IP Address), etc.		
Others	Mobile Surveillance Support		
	Power Supply DC 12V3A		
	Power Consumption (Without HDD) < 10W(Without HDD)		
	Working Temperature -10°C~+55°C		
	Working Humidity 10%~90%		
	Dimension NVR: 1.5U, 350mm(W)*240mm(L)*68mm(H); Packing: 414mm*370mm*134mm		
	Weight(Without HDD) N.W: 1.7KG; With Packing: 2.9KG		
	Carton 5pcs/Carton; Dimension:675mm*425mm*385mm; Weight:15.3 KG		
	Installation Desktop Installation		

### Dimension (Unit : mm)

