

NVR-4136HGK

Linux Network Video Recorder



FEATURE

- The Preview Screen can be changed at will, The Image Position changed, The Physical Address will not be changed;
- Support 15X Digital Enlarge, Dragging any Enlarged Image by Mouse (Preview/Playback);
- Support Instant Capture, and set a Separate-Area to save the Screenshot in the HDD ;
- Recording Playback is shown by Time Bar, Different Colors displays Different Recording Type, Fast and Easy for checking the Recording;
- Support USB Disk Backup File Playback on Host Directly (Backup can be accurate to the seconds);
- HDD Sequence Writing Method, start writing Data from zero tracks, Enhance the Efficiency of HDD Read and Write;

SPECIFICATION

Model No.	NVR-4136HGK	
Operating System	Embedded Linux Operating System	
Image Coding Control	Image Coding Quality can be adjusted, VBR / CBR Optional	
Dual Stream	Each Channel can be set	
Video Standard	H.265/H.264	
Image Quality	4K(3840*2160)/4MP(2560*1600)/1080P(1920*1080) / 960P(1280*960) / 720P(1280*720)	
Image Dynamic Detection	Each Screen can detect Multiple Detection Regions, 6 levels Sensitivity can be set (IPC Support Needed)	
Image Playback	1/4/9/16CH Sync. Playback	
Privacy Mask	Each Channel support 4 Privacy Mask Areas (need IPC support);	
Recording Mode	Support Manual, Auto, Dynamic Detection, Alarm Trigger Recording Mode	
Backup Mode	Support HDD, U Disk, USB Mobile HDD, USB Record, Network Storage and Backups (Partly need IPC support);	
Operating Mode	Mouse, Keyboard	
Local Login	User Name / Password	
Recording Storage	Local HDD, Remote Network Host	
External Interface	Network Video Input	① 36x[3840*2160]+sub[960*576]+4Ref.+4Play ② 36x[2048*1536]+sub[960*576]+4Ref.+9Play ③ 36x[1920*1080]+sub[960*576]+4Ref.+16Play
	Audio Input	1:1 Network Audio Input by Network Video Channel Number;
	Video Output	1CH VGA + 1CH HDMI
	Audio Output	1*RCA
	Network Interface	1*RJ45
	RS485 Interface	Full Duplex Standard RS485 Interface
	USB Interface	1*USB3.0 Interface, 2*USB2.0 Interface
	Alarm Input	4ch
	Alarm Output	1ch
HDD	Interface	4*SATA
	Max. Capacity	Each SATA Interface support Max. 6TB HDD;
Mobile Surveillance	Support	
Power Supply	12V6A	
Consumption	≤25W (without HDD)	
Working Temperature	-10°C~+55°C	
Working Humidity	10%-90%	
Dimension	Equipment: 440mm×356mm×68.5mm, With Package: 460mm×135mm×560mm	
Weight(without HDD)	Net Weight: 5.7Kg; with Package: 6.9Kg	
Carton	4pcs 1 carton. Dimension: 480mm×560mm×575mm; Weight: 30Kg.	
Installation	Desktop Installation, Standard Rack Installation	

Dimension (Unit : mm)

