

NVR-9136HGK

NVR-9164HGK

Embedded HD Network Video Recorder



Features

- The Preview Screen can be changed at will, The Image Position changed, The Physical Address will not be changed;
- Support 15X Digital Enlarge, Dragging any Enlarged Image by Mouse(Preview/Playback);
- Support Instant Capture, and set a Separate-Area to save the Screenshot in the HDD ;
- Recording Playback is shown by Time Bar, Different Colors displays Different Recording Type, Fast and Easy for checking the Recording;
- Support USB Disk Backup File Playback on Host Directly(Backup can be accurate to the seconds);
- HDD Sequence Writing Method, start writing Data from zero tracks, Enhance the Efficiency of HDD Read and Write;

Specifications

Model No.	NVR-9136HGK	NVR-9164HGK	
Operating System	Embedded Linux Operating System		
Image Coding Control	Image Coding Quality can be adjusted, VBR/ CBR Optional		
Dual Stream	Each Channel can be set		
Video Standard	H.265/ H.264		
Image Quality	4K(3840×2160)/5MP(2592×1944)/3MP(2048×1536)/1.080P(1920×1080)/960P(1280×960)/720P(1280×720)		
Image Dynamic Detection	Each Screen can detect Multiple Detection Regions, 6 levels Sensitivity can be set		
Image Playback	1 1/4/9/16CH Sync. Playback	1/4/9/16CH Sync. Playback	
Privacy Mask	Each Channel support 4 Privacy Mask Areas (need IPC support);		
Recording Mode	Support Manual, Auto, Dynamic Detection, Alarm Trigger Recording Mode		
Backup Mode	Support Hard Disk, U Disk, USB Mobile Hard Disk, USB Record, Network Storage and Backups (Partly need IPC support);		
Operating Mode	Mouse, Keyboard		
Local Login	User Name / Password		
Recording Storage	Local Hard Disk, Remote Network Host		
External Interface	Network Video Input	① 36×[3840*2160]+sub[960*576]+4Ref.+4Play	① 64×[3840*2160]+sub[960*576]+4Ref.+4Play
		② 36×[2048*1944]+sub[960*576]+4Ref.+9Play	② 64×[2048*1944]+sub[960*576]+4Ref.+9Play
		③ 36×[1920*1080]+sub[960*576]+4Ref.+16Play	③ 64×[1920*1080]+sub[960*576]+4Ref.+16Play
	Audio Input	1:1 Network Audio Input by Network Video Channel Number;	
	Video Output	1CH VGA + 1CH HDMI	
	Audio Output	1*RCA	
	Network Interface	1*RJ45	*RJ45
	S485 Interface	Full Duplex Standard RS485 Interface	
	USB Interface	1*USB3.0 Interface, 2*USB2.0 Interface	
Alarm Input	4ch		
Alarm Output	4ch		
Hard Disk	Hard Disk Interface	9*SATA+1*E-SATA	
	Max. Capacity	each SATA Interface support Max. 6TB Hard Disk;	
Mobile Surveillance	Support		
Power Supply	ATX110-220V 200W 50-60Hz		
Consumption	≤30W (without HDD)		
Working Temperature	-10°C~+55°C		
Working Humidity	10%-90%		
Dimension	440mm×432mm×90mm, With Package: 539mm×550mm×225mm		
Weight(without HDD)	Net Weight: 7.4Kg; with Package: 9.8Kg		
Carton	2pcs 1 carton. Dimension: 555mm×545mm×470mm; Weight: 21 Kg.		
Installation	Desktop Installation, Standard Rack Installation		

Dimension (Unit : mm)

